

Parametry jednokřídlových klapek FIRE

Poř. č.	Jmenovité rozměry otvorů [cm]			Geometrická plocha [m ²]	Aktivní plocha [m ²]			Hmotnost klapky [kg] *	Typ pohonu, elektrický příkon	
	Délka A	Šířka B	Výška H		Klapky	Klapky s deflektory	Klapky s deflektory a tryskou			
1	100	100	50	1,00	0,47	0,77	0,82	51	ZA 155/800-HS; 2,5 A nebo ZA 155/800-K-BSY+HS; 105 VA	
2	100	110	50	1,10	0,51	0,85	0,90	53		
3	100	120	50	1,20	0,55	0,91	0,98	56		
4	100	130	50	1,30	0,59	0,98	1,07	58		
5	100	140	50	1,40	0,63	1,05	1,16	61		
6	100	150	50	1,50	0,66	1,13	1,25	63		
7	100	160	50	1,60	0,69	1,18	1,33	66		
8	100	170	50	1,70	0,73	1,26	1,41	68		
9	100	180	50	1,80	0,76	1,33	1,49	74		
10	100	190	50	1,90	0,78	1,41	1,58	73		
11	100	200	50	2,00	0,82	1,46	1,66	76	DXD 300/800-BSY+HS; 5 A ZA 155/800-HS; 2,5 A nebo ZA 155/800-K-BSY+HS; 105 VA DXD 300/800-K-BSY+HS; 175 VA	
12	100	210	50	2,10	0,84	1,53	1,74	78	DXD 300/800-BSY+HS; 5 A nebo DXD 300/800-K-BSY+HS; 175 VA	
13	100	220	50	2,20	0,88	1,61	1,83	81		
14	110	110	50	1,21	0,58	0,92	0,99	55	ZA 155/800-HS; 2,5 A nebo ZA 155/800-K-BSY+HS; 105 VA	
15	110	120	50	1,32	0,62	0,99	1,08	58		
16	110	130	50	1,43	0,67	1,07	1,19	60		
17	110	140	50	1,54	0,71	1,14	1,28	63		
18	110	150	50	1,65	0,76	1,22	1,37	65		
19	110	160	50	1,76	0,79	1,30	1,46	68		
20	110	170	50	1,87	0,84	1,37	1,55	70		
21	110	180	50	1,98	0,87	1,45	1,64	73		
22	110	190	50	2,09	0,92	1,53	1,73	75	DXD 300/800-BSY+HS; 5 A ZA 155/800-HS; 2,5 A nebo ZA 155/800-K-BSY+HS; 105 VA DXD 300/800-K-BSY+HS; 175 VA	
23	110	200	50	2,20	0,95	1,61	1,83	77	DXD 300/800-BSY+HS; 5 A nebo DXD 300/800-K-BSY+HS; 175 VA	
24	110	210	50	2,31	0,97	1,66	1,92	80		
25	110	220	50	2,42	1,02	1,74	2,01	83		
26	115	115	50	1,32	0,65	0,99	1,08	58	ZA 155/800-HS; 2,5 A nebo ZA 155/800-K-BSY+HS; 105 VA	
27	120	120	50	1,44	0,71	1,08	1,20	61	ZA 155/1000-HS; 2,5 A nebo ZA 155/1000-K-BSY+HS; 105 VA	
28	120	130	50	1,56	0,75	1,15	1,29	63		
29	120	140	50	1,68	0,81	1,24	1,39	66		
30	120	150	50	1,80	0,85	1,31	1,49	68		
31	120	160	50	1,92	0,90	1,40	1,59	71		
32	120	170	50	2,04	0,94	1,49	1,69	73		
33	120	180	50	2,16	0,99	1,56	1,79	76	DXD 300/800-BSY+HS; 5 A ZA 155/800-HS; 2,5 A nebo ZA 155/800-K-BSY+HS; 105 VA DXD 300/800-K-BSY+HS; 175 VA	
34	120	190	50	2,28	1,03	1,64	1,89	78	DXD 300/1000-BSY+HS; 5 A nebo DXD 300/1000-K-BSY+HS; 175 VA	
35	120	200	50	2,40	1,08	1,73	1,99	81		
36	120	210	50	2,52	1,11	1,81	2,09	83	ZA 155/1000-HS; 2,5 A nebo ZA 155/1000-K-BSY+HS; 105 VA	
37	120	220	50	2,64	1,16	1,90	2,19	86		
38	125	125	50	1,56	0,77	1,16	1,30	63		
39	130	130	50	1,69	0,85	1,25	1,40	65		
40	130	140	50	1,82	0,89	1,33	1,51	68		
41	130	150	50	1,95	0,96	1,42	1,62	70		
42	130	160	50	2,08	1,00	1,52	1,73	73	ZA 155/1000-K-BSY+HS; 105 VA	
43	130	170	50	2,21	1,06	1,59	1,83	75	DXD 300/800-BSY+HS; 5 A ZA 155/800-HS; 2,5 A nebo ZA 155/800-K-BSY+HS; 105 VA DXD 300/800-K-BSY+HS; 175 VA	
44	130	180	50	2,34	1,10	1,68	1,94	78	DXD 300/1000-BSY+HS; 5 A nebo DXD 300/1000-K-BSY+HS; 175 VA	
45	130	190	50	2,47	1,16	1,78	2,05	80		
46	130	200	50	2,60	1,20	1,87	2,16	83		
47	130	210	50	2,73	1,26	1,94	2,27	85		
48	130	220	50	2,86	1,29	2,03	2,37	88		
49	140	140	50	1,96	1,00	1,43	1,63	71	ZA 155/1000-HS; 2,5 A nebo ZA 155/1000-K-BSY+HS; 105 VA	
50	140	150	50	2,10	1,05	1,51	1,74	73	ZA 155/1000-K-BSY+HS; 105 VA	
51	140	160	50	2,24	1,12	1,61	1,86	76	DXD 300/800-BSY+HS; 5 A ZA 155/800-HS; 2,5 A nebo ZA 155/800-K-BSY+HS; 105 VA DXD 300/800-K-BSY+HS; 175 VA	
52	140	170	50	2,38	1,17	1,71	1,98	78	DXD 300/1000-BSY+HS; 5 A nebo DXD 300/1000-K-BSY+HS; 175 VA	
53	140	180	50	2,52	1,23	1,81	2,09	81		
54	140	190	50	2,66	1,28	1,89	2,21	83	DXD 300/1000-K-BSY+HS; 175 VA	
55	140	200	50	2,80	1,34	1,99	2,32	85		
56	150	150	50	2,25	1,15	1,62	1,87	76		DXD 300/1000-BSY+HS; 5 A nebo DXD 300/1000-K-BSY+HS; 175 VA
57	150	160	50	2,40	1,22	1,73	1,99	79		
58	150	170	50	2,55	1,28	1,81	2,12	81		
59	150	180	50	2,70	1,35	1,92	2,24	84		
60	150	190	50	2,85	1,43	2,02	2,37	86		
61	160	160	50	2,56	1,33	1,82	2,12	81		
62	160	170	50	2,72	1,39	1,93	2,26	83		
63	160	180	50	2,88	1,47	2,04	2,39	89		

* hmotnost klapky netto = hmotnost klapky brutto (klapky jsou balené do bublinkové fólie); v případě klapky s deflektory přidejte navíc 4 kg.